

wattyl®

SPRAY SOLUTIONS GUIDE



**ULTRA
FINISH
TECHNOLOGY**

High efficiency spray application products for walls and ceilings designed for large commercial and residential projects.

**ULTRA
FINISH
TECHNOLOGY**

Wattyl Ultra is a professional paint system formulated with Ultra Finish Technology for superior application and a professional finish.



USES

Suitable for prep coat over walls and ceilings:

- previously painted surfaces
- new paper-faced plasterboard
- unpainted brick, cement render, fibre cement or masonry
- bare timber & MDF (except for tannin rich timbers where a first coat of Wattyl Ultra Primer Sealer Undercoat will be required)
- VOC Level <14g/L

APAS
AUSTRALIAN PAINTS PROFESSIONAL SCHEME
0260/5

[^] Due to the high opacity of the product tinted colours will appear lighter than the standard colour

HIGH EFFICIENCY FLAT

Wattyl Ultra Prep+Ceiling High Efficiency Flat is a premium quality, water-based sealer-undercoat and ceiling coating. Developed for spray application and to deliver high work efficiency in commercial and residential environments. It provides a sound base for subsequent topcoats on interior walls and ceilings and an ultra flat high coverage ceiling finish.

FEATURES AND BENEFITS

- Designed to spray both walls and ceilings in one application
- Save time by reducing cutting in on ceiling
- No need to change products between undercoating and ceiling finish
- Built for airless spraying and developed for spray and back roll application
- Low VOC
- Easy, fast application
- Smooth uniform flat finish

APPLICATION

Apply one full even coat as a sealer-undercoat using airless spray and backroll.

On ceiling apply further finishing coats by airless spray and backroll.

Suggested spray setting: 517 spray tip at 2000-2300psi

SIZES: 10L, 15L





- Dual-purpose Prep+Ceiling in one
- Designed for fast spray application

NEW



USES

Suitable for prep coat over walls and ceilings:

- previously painted surfaces
- new paper-faced plasterboard
- unpainted brick, cement render, fibre cement or masonry
- bare timber & MDF (except for tannin rich timbers where a first coat of Watty Ultra Primer Sealer Undercoat will be required)
- VOC Level <28g/L



[^] Due to the high opacity of the product tinted colours will appear lighter than the standard colour

SURFACE PRO FLAT

Watty Ultra Prep+Ceiling Surface Pro Flat is a 100% acrylic high opacity high build base / finish coat which can assist in creating a level 5 finish on interior paper-faced plasterboard surfaces. It applies quickly and evenly with professional application methods. In ceiling applications where a flat finish is desired, Watty Ultra Prep+Ceiling Surface Pro is a sealer and finish coat in one.

FEATURES AND BENEFITS

- Designed to assist in creating a "Level 5 finish"
- Designed to spray both walls and ceilings in one application
- High build primer and ceiling finish
- Minimises surface imperfections
- Flat, smooth, uniform, even finish
- Designed for critical light applications
- Easy, fast application
- Can be used on walls and woodwork to minimise preparation requirements

APPLICATION

This product is recommended for airless spray application only. Apply using a cross hatch application method wet on wet in manageable sections e.g. 2.5m x 2.5m. Recommended tip size is 21 thou; recommended pressure is 3000psi.

SIZES: 10L, 15L



wattyl[®]

Don't worry,
whatever you need,
we can help.

For further information refer to the Technical Data Sheets available on our website, or contact your local sales representative.

Sherwin-Williams Australia. Level 4, 2 Burbank Place, Baulkham Hills NSW 2153.
Sherwin-Williams New Zealand. 4-14 Patiki Road, Avondale.

11/18 WAT18015



AUS 132 101
wattyl.com.au

NZ 0800 825 7727
wattyl.co.nz